

Technical Specifications

STARVIS 4K IR Bullet IP Camera

FOR EXTERNAL APPLICATION

- 8MP at 30fps
- H.265, H.264 and MJPEG video compression
- WaveIR: Advanced Smart IR low light Performance
- Remote Zoom & focus Motorized lens
- WaveCapture: Smart Advanced Wide Dynamic Capture for high details in challenging conditions
- WaveStream: Smart Compression Technology based on bit rate Control, ROI
- WaveVCA*: Intelligence built-in Camera Analytics
- 12V DC & Power Over Ethernet (IEEE 802.3af)
- IP66 & IK10 Environmental housing



















CAMERA	
Model	IP-30503LBO Outdoor, Motorized Focus & Zoom lens
Image Sensor	SONY STARVIS EXMOR 1/1.8" 8.5MP CMOS
Effective Pixels	3952(H) x 2320(V)
Scanning System	Progressive scanning
AGC Control	Auto
IRIS Type	P-IRIS
Minimum Illumination	Color: 0.09 Lux / B/W : 0 Lux (IR LED On)
Lens	3.6 – 10 mm, F1.5
Angle of View	Dimension: Approx. 112.9° (Wide) to 52.3° (Tele) Horizontal: Approx. 98.4° (Wide) to 45.7° (Tele) Vertical: Approx. 54.6° (Wide) to 25.9° (Tele)
Shutter Speed	Auto / Manual (1/15 ~ 1/32000), Anti-Flicker, Slow Shutter(2X, 3X, 5X, 6X, 7.5X, 10X)
Day & Night	True Day & Night (Removable IR-cut filter)
Wide Dynamic Range	True WDR, 120 dB or above
Smart Capture Technology	WaveCapture : Smart Advanced Wide Dynamic Capture for high details in challenging conditions
S/N Ratio	50 Db

IR ILLUMINATOR	
Smart IR	WaveIR :- Advanced Smart IR
IR Working Distance	120ft
VIDEO	
Video Compression	H.265, H.264, MJPEG
Profile	H.264 : MP / HP H.265 : MP
Multiple Profile Streaming Performance	3840x2160p30 + 480p30 with H.264, H265 + MJPEG
Max Resolution	3840 x 2160
Video Bit Rate	100Kbps ~ 10Mbps Multi-rate for Preview and Recording
Bitrate Control	Multi Streaming CBR/VBR (Controllable frame rate and Bandwidth)
Digital Noise Reduction	3D-DNR
Privacy Mask	16 programmable zones
Special Features	Wavestream: Smart Compression Technology based on bit rate Control- Region of Interest
Other Image Processing	Configurable Exposure, White Balance, Sharpness

Technical Specifications

AUDIO	
Audio Streaming	Two way
Audio Compression	G.711
Audio input	1[1.0Vms, 3K ohm]
Audio Output	1
DI/DO	1/1

EVENT	
Event Trigger	Motion Alarm, Temperature critical, Network disconnection
Smart Edge Analytics*	WaveVCA: Intelligence built-in Cameras Analytics*
Pre-Post Recording	Pre: 1~5 sec Post: 1~240 sec
Event Notification	FTP, E-mail, Alarm-out, SD card
Storage	1x microSD / microSDHC / microSDXC (card not included)

NETWORK	
Ethernet Standard	10 / 100 / 1000Base-T
Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF
Security	HTTPS(SSL), IP filtering, 802.1x, Digest Authentication
Plug In	ONVIF Profile S, CGI API

GENERAL	
Material	Aluminum Die-casting, White
Housing Environmental Rating	IP66
Housing Impact Rating	IK10
External I/O Terminals	1 x Alarm In / 1 x Alarm Out
Power Source	DC12V, PoE+(IEEE 802.3af)
Power Consumption	Below 16W
Operating Conditions	Humidity 10 ~ 90% RH (non-condensing) [DC12V / PoE] -40°C ~ 50°C (-40°F ~ 122°F)
Approvals	FCC, CE, ROHS, BIS
Weight	0.9 kg
Dimensions (D x H)	247.2mm x 96.7mm

WaveVCA: Intelligence built-in Cameras Analytics

Basic features

Analytics Engine VCA Technology's advanced tracking algorithm with rich library of detection behaviors

Detection Zones and Rules 40 zones (Multisegment Polygons and Lines) in total, 60 rules in total as standard

Intrusion Detection Detection of the presence of an object

Tamper Detection Supported as standard

Basic features*







Zones & lines



Tamper Detection



Shake Cancellation

Optional features*



Appear & Disappear Filter



Stopped Filter



Dwell Enter & Exit Filter Filters



Tailgating Filter



Speed Filter



3D Calibration



Object Counting







Colour Filter



Abandoned Object Filter



Removed Object Filter




Direction Filter




Logical Rules

Technical Specifications

Dimensions (Unit: mm)





Accessories



W-BP07